

Deep Learning - Part 1

Aymeric DIEULEVEUT

DS4M - April 2025

1 Goals

- ## 2 The first Neural Network: the Perceptron
- Logistic regression
 - Discovering Fully connected NN through the NNPG.
 - Formalization, advanced topics
 - Further discussion

Outline

1 Goals

- ## 2 The first Neural Network: the Perceptron
- Logistic regression
 - Discovering Fully connected NN through the NNPG.
 - Formalization, advanced topics
 - Further discussion

Deep Learning in one slide + Goals of the afternoon

- **How does it work:**

- ▶ Automatically learn representations of observations
- ▶ Learn highly non-linear models.

- **What does it require:**

- ▶ Large datasets with structure
- ▶ Computational power

- **Why now:**

- ▶ Combination of the 2 points above
- ▶ investment !


- **Some Applications**

- ▶ Image classification; object / face recognition
- ▶ Self driving cars
- ▶ Automatic Translation, Information extraction
- ▶ Caption Generation
- ▶ Ads, recommendation systems, etc.

Goals: Understanding core concepts of Deep Learning.


- When and how it works on paper (data, models, architecture)
- How to implement a simple neural network with Python.
- Overview of some of the main applications and challenges.

Machine Learning



Summary of previous lectures on Machine Learning

① General framework: loss, risk, generalization risk vs training risk



Loss function, Generalization Risk and data-dependent predictors

Loss Function

- Loss function: $\ell(y, g(x))$ quantifies the quality of the prediction $g(x)$ of y , e.g.:
 - ▶ 0-1 Loss (classification): $\ell(y, g(x)) = 1_{y \neq g(x)}$, $y \in \mathcal{Y} = \{-1, 1\}$
 - ▶ Quadratic Loss (regression): $\ell(y, g(x)) = \|y - g(x)\|^2$, $y \in \mathbb{R}^d$

Risk of a Decision Rule = average loss

- Risk: $R(g) = \mathbb{E}[\ell(Y, g(x))] = \int \ell(y, g(x)) d\mathbb{P}(x, y)$, e.g.:
 - ▶ 0-1 Risk (classification): $R(g) = \mathbb{P}(Y \neq g(x))$
 - ▶ Quadratic Risk (regression): $R(g) = \mathbb{E}[|Y - g(x)|^2]$
- ↪ R is also referred to as *Generalization risk*, or *True risk*.

⚠ The distribution $\mathbb{P}$ is unknown.

Data-dependent predictors

- **Training set:** $\mathcal{D}_n = \{(X_1, Y_1), \dots, (X_n, Y_n)\}$ (i.i.d. $\sim \mathbb{P}$)
- Goal: build a **data dependent predictor / classifier** $\hat{g}_n$ based on the training data
- That has a **minimal generalization risk** $R(\hat{g}_n)$.


$R(\hat{g}_n)$ = average loss on a "new point" $(X, Y) \sim \mathbb{P}$, independent from $\mathcal{D}_n$

↔ Our goal is to predict well on inputs/outputs pairs that **we have not seen in the dataset**, i.e. *generalize well*.

THM 1.


Summary of previous lectures on Machine Learning

- 1 General framework: loss, risk, generalization risk vs training risk
- 2 SML Pipeline
 - ▶ Train (Fit + validation) / Test / Deployment
 - ▶ Evaluation of validation scores through cross validation to pick the best method/hyperparams




Summary of previous lectures on Machine Learning

- 1 General framework: loss, risk, generalization risk vs training risk
- 2 SML Pipeline
 - ▶ Train (Fit + validation) / Test / Deployment
 - ▶ Evaluation of validation scores through cross validation to pick the best method/hyperparams
- 3 Methods: Linear, Logistic regression, Decision Trees, Random Forests, Boosting



Fitting algo.
Learn $\hat{f}_n =$
i.e. weight $\hat{w}$
bias $\hat{b}$



Summary of previous lectures on Machine Learning

- ① General framework: loss, risk, generalization risk vs training risk
- ② SML Pipeline
 - ▶ Train (Fit + validation) / Test / Deployment
 - ▶ Evaluation of validation scores through cross validation to pick the best method/hyperparams
- ③ Methods: Linear, Logistic regression, Decision Trees, Random Forests, Boosting
- ④ Opening the black box: for each method
 - ▶ How to predict (↔ interpretability)
 - ▶ How fit is made (↔ speed, complexity) [Computer learning parameters]
 - ▶ Important Hyper-parameters [User chosen]
 - ▶ Drawbacks and Strengths
 - ▶ Underfitting, overfitting risks (↔ Performance)
 - regularization techniques (avoiding overfitting by modifying the method)

$\hat{f}_n = \square$

: Lin. Reg

Polynomial
Linear reg

Logistic Reg

Dec Trees

RF/Boosting

How to predict

How to fit

Key hyperparameters

$\oplus$

$\ominus$

Overfitting / Underfitting
 $\hookrightarrow$ regularization technique

Approach

Outline

1 Goals

- ## 2 The first Neural Network: the Perceptron
- Logistic regression
 - Discovering Fully connected NN through the NNPG.
 - Formalization, advanced topics
 - Further discussion

Outline

1 Goals

2 The first Neural Network: the Perceptron

- Logistic regression
- Discovering Fully connected NN through the NNPG.
- Formalization, advanced topics
- Further discussion

From logistic regression to Multi Layer Perceptron 1

Supervised ML problem:

- ① Data $D_n = (X_i, Y_i)_{i=1, \dots, n}$, $X_i \in \mathbb{R}^d$, $Y_i \in \{-1, 1\}$
- ② Goal: Predict a the label for a new point.

Empirical risk minimization (Discriminative approach)

- No statistical model!
- Define a loss function ℓ
- Choose a function class $\mathcal{F}$
- Goal:

$$\min_{f \in \mathcal{F}} \mathbb{E}[\ell(f(X), Y)]$$

- ERM

$$\min_{f \in \mathcal{F}} \frac{1}{n} \sum_{i=1}^n [\ell(f(X_i), Y_i)]$$

Linear models

Class of *soft* linear separators:

$$\mathcal{F}_{lin} = \{g_w : X \mapsto w^\top X, w \in \mathbb{R}^d\}$$

Binary prediction from a soft predictor: $X \mapsto \text{sign}(w^\top X)$

Linear models

Class of *soft* linear separators:

$$\mathcal{F}_{lin} = \{g_w : X \mapsto w^\top X, w \in \mathbb{R}^d\}$$

Binary prediction from a soft predictor: $X \mapsto \text{sign}(w^\top X)$

01 loss:

$$\frac{1}{n} \sum_{i=1}^n 1_{Y_i \neq \text{sign}(w^\top X_i)} = \frac{1}{n} \sum_{i=1}^n 1_{-Y_i w^\top X_i > 0}$$

Logistic regression loss

$$\frac{1}{n} \sum_{i=1}^n \log(1 + \exp(-Y_i w^\top X_i))$$

Outline

1 Goals

2 The first Neural Network: the Perceptron



- Logistic regression
- **Discovering Fully connected NN through the NNPG.**
- Formalization, advanced topics
- Further discussion

Let's NN playground: [Link](#)

1. Understand what the features are. Understand what colors represent.


FEATURES

Which properties do you want to feed in?



Let's NN playground: [Link](#)


2. Consider the simplest dataset, an 0 hidden layer. **Manually pick weights to obtain a good classification.**



What model does this correspond to? How many weights does it have?

Let's NN playground: [Link](#)


2. Consider the simplest dataset, an 0 hidden layer. **Manually pick weights to obtain a good classification.**



What model does this correspond to? How many weights does it have?

Let's NN playground: [Link](#)


3. Consider the simplest dataset, an 0 hidden layer. Instead of manually tuning the weights, obtain them by **fitting**!



What algorithm are we running?
What can you say about the loss?
Rerun the algorithm? What happens?

Let's NN playground: [Link](#)


3. Consider the simplest dataset, an 0 hidden layer. Instead of manually tuning the weights, obtain them by **fitting**!



What algorithm are we running?
What can you say about the loss?
Rerun the algorithm? What happens?

Let's NN playground: [Link](#)


4. Increase the data noise to 15. Is the data linearly separable then? Run 3 times for 1000 epochs, compare the weights obtained



What do you conclude / confirm on logistic regression?

Let's NN playground: [Link](#)

5. Change the dataset to . Run logistic regression. What do you observe?




What do you suggest?

Let's NN playground: [Link](#)

6. Add a single hidden layer, first with a single neuron, then with 4 neurons.
Keep only features X^1 and X^2 .

Let's NN playground: [Link](#)

6. Add a single hidden layer, first with a single neuron, then with 4 neurons. Keep only features X^1 and X^2 .



What do you observe?

What have we learned?

How does that illustrate *feature learning*?

What happens if you restart learning?


Let's NN playground: [Link](#)

6. Switch to the more complex spiral dataset . Increase the number of neurons. Fit the model.

Keep only features X^1 and X^2 .

Let's NN playground: [Link](#)

6. Switch to the more complex spiral dataset . Increase the number of neurons. Fit the model.
Keep only features X^1 and X^2 .




What happens? How stable is the training?

How many weights are you learning now? Are there biases? What are those?


Let's NN playground: [Link](#)

6. Switch to the more complex spiral dataset . Increase the number of neurons. Fit the model.
Keep only features X^1 and X^2 .



OUTPUT

Test loss 0.261
Training loss 0.173




What can you say about the algorithm dynamic ?

Let's NN playground: [Link](#)

6. Switch to the more complex spiral dataset . Increase the number of neurons. Fit the model.

Keep only features X^1 and X^2 .



What do you suggest next?

Let's NN playground: [Link](#)




7. Explore configurations : what do you obtain?

Let's NN playground: [Link](#)

7. Explore configurations : what do you obtain? What is the role of the activation function? What happens for a deep architecture for Linear / Sigmoid / Relu / Tanh?

Let's NN playground: [Link](#)

7. Explore configurations : what do you obtain? What is the role of the activation function? What happens for a deep architecture for Linear / Sigmoid / Relu / Tanh?




Let's NN playground: [Link](#)

8. How do the features learned evolve depending on the layer?

Let's NN playground: [Link](#)

8. How do the features learned evolve depending on the layer?



Let's NN playground: [Link](#)

9. What are the hyper-parameters of the SGD algorithm? Play with them.

Advanced

- ① What happens if you initialize all weights to 0?

Conclusion on NNPG

① “Architecture”:

② What we have seen

③ *Protip*

Wooclap time!



- 1 Allez sur wooclap.com
- 2 Entrez le code d'événement dans le bandeau supérieur

Code d'événement
BLCOFS



- 1 Envoyez **@BLCOFS** au **06 44 60 96 62**
- 2 Vous pouvez participer

 Désactiver les réponses par SMS

Outline



1 Goals

2 The first Neural Network: the Perceptron

- Logistic regression
- Discovering Fully connected NN through the NNPG.
- **Formalization, advanced topics**
- Further discussion

From logistic regression to Multi Layer Perceptron 3


- Class of functions for logistic regression: $\mathcal{F} = \{X \mapsto w^T X, w \in \mathbb{R}^d\}$.
- Prediction for a new point is $1_{\sigma(X_i) > 1/2}$
- Can be seen as predicting a probability $\sigma(X_i)$ that the output is 1



This is a neural network, with one neuron !

From logistic regression to Multi Layer Perceptron 3

- Class of functions for logistic regression: $\mathcal{F} = \{X \mapsto w^T X, w \in \mathbb{R}^d\}$.
- Prediction for a new point is $1_{\sigma(X_i) > 1/2}$
- Can be seen as predicting a probability $\sigma(X_i)$ that the output is 1




This is a neural network, with one neuron !

From logistic regression to Multi Layer Perceptron 4

Extend to


- Multiple Neurons
- Multiple Layers



From logistic regression to Multi Layer Perceptron 4

Extend to


- Multiple Neurons
- Multiple Layers



From logistic regression to Multi Layer Perceptron 5

Extend to

- Multiple Neurons
- Multiple Layers




From logistic regression to Multi Layer Perceptron 5

Neural network:

- Goal $\min_{f \in \mathcal{F}_{\text{MLP}}} \frac{1}{n} \sum_{i=1}^n [\ell(f(X_i), Y_i)]$

- Class of non linear functions.

$$\mathcal{F}_{\text{MLP}} = \{f(X; W, b) = \sigma(b_n + W_n \sigma(\dots(b_1 + W_1 x)))\},$$
$$W \in \mathbb{R}^{\dots}, b \in \mathbb{R}^{\dots}\}$$



Summary: NN generalize regression by looking for candidates in a much larger class of functions than linear ones.

What needs to be learned

What needs to be chosen

Vocabulary


From logistic regression to Multi Layer Perceptron 5

Neural network:

- **Goal** $\min_{f \in \mathcal{F}_{\text{MLP}}} \frac{1}{n} \sum_{i=1}^n [\ell(f(X_i), Y_i)]$

- Class of non linear functions.

$$\mathcal{F}_{\text{MLP}} = \{f(X; W, b) = \sigma(b_n + W_n \sigma(\dots(b_1 + W_1 x))\},$$
$$W \in \mathbb{R}^{\dots}, b \in \mathbb{R}^{\dots}\}$$



Summary: NN generalize regression by looking for candidates in a much larger class of functions than linear ones.

What needs to be learned

Parameters W, b


What needs to be chosen

- Activation σ
- Number of layers L
- Number of neurons per hidden layer
 $n_i, i = 1, \dots, L.$

Vocabulary


- Neuron
- Activation
- Hidden Layer
- Width, Depth
- Fully connected layer

2 possible activations: Sigmoid and Rectified Linear Unit



Sigmoid function

- $x \mapsto \frac{\exp(x)}{1 + \exp(x)}$
- Problems:
 - 1 Saturated function: gradient killer -> need for rescaling data



Rectified Linear Unit (ReLU)

- $x \mapsto \max(0, x)$
- Pros & cons:
 - 1 Not a saturated function. Kills negative values.
 - 2 Empirically, **convergence is faster** than sigmoid/tanh.
 - 3 Plus: **biologically plausible**

How to deal with multi-class output: softmax activation

When we do multi-class classification, i.e., $Y_i \in 1, \dots, K$, we output K different values:

- Each of them corresponds to the probability of belonging to the class j , $1 \leq j \leq K$
- To obtain probabilities (adding up to 1):
 - ① We have K neurons on the last layer
 - ② And use a Softmax activation to renormalize.

Softmax output unit, used to predict $\{1, \dots, K\}$:

$$\text{softmax}(z)_i = \frac{e^{z_i}}{\sum_{k=1}^K e^{z_k}}$$

Up to that point, we have seen :

- What a Neural Network was
- Why it is expected to learn better.

Next Question: how to implement it ?

Python - Keras

1. Hardware:

- CPU
- GPU
- TPU

2. Software (Python packages):

- Pytorch/Tensorflow
- → Keras : TF high level API. Ideal for applications.



PyTorch



Keras

Keras - A few lines !¹

What do we need to specify?

What do we need to do next?

```
# import tensorflow and keras (tf.keras not "vanilla" Keras)
import tensorflow as tf
from tensorflow import keras
# get data
(train_images, train_labels), (test_images,
                                test_labels) = keras.datasets.mnist.load_data()

# setup model
model = keras.Sequential([
    keras.layers.Flatten(input_shape=(28, 28)),
    keras.layers.Dense(128, activation=tf.nn.relu),
    keras.layers.Dense(64, activation= tf.nn.relu),
    keras.layers.Dense(10, activation=tf.nn.softmax)
])

model.compile(optimizer=tf.optimizers.Adam(),
              loss='sparse_categorical_crossentropy',
              metrics=['accuracy'])
# train models
model.fit(train_images, train_labels, epochs=5)

print('\n Evaluation' )
# evaluate
test_loss, test_acc = model.evaluate(test_images, test_labels)
print('test accuracy:', test_acc)
# make predictions
predictions = model.predict(test_images)
```

Wooclap!



```
# import tensorflow and keras (tf.keras not "vanilla" Keras)
import tensorflow as tf
from tensorflow import keras
# get data
(train_images, train_labels), (test_images,
                                test_labels) = keras.datasets.mnist.load_data()

# setup model
model = keras.Sequential([
    keras.layers.Flatten(input_shape=(28, 28)),
    keras.layers.Dense(128, activation=tf.nn.relu),
    keras.layers.Dense(64, activation= tf.nn.relu),
    keras.layers.Dense(10, activation=tf.nn.softmax)
])

model.compile(optimizer=tf.optimizers.Adam(),
              loss='sparse_categorical_crossentropy',
              metrics=['accuracy'])
# train models
model.fit(train_images, train_labels, epochs=5)

print('\n Evaluation' )
# evaluate
test_loss, test_acc = model.evaluate(test_images, test_labels)
print('test accuracy:', test_acc)
# make predictions
predictions = model.predict(test_images)
```



What can you say about this code bit

- ☐
☒
- 1 The flatten layer is a dense layer
 - 2 I have 2 hidden layers
 - 3 I have one hidden layer
 - 4 I should use sigmoid activation on the last layer
 - 5 I use SGD for the algorithm
 - 6 AdamOptimizer is EveOptimizer's boyfriend
 - 7 I run 5 epochs of the stochastic algorithm
 - 8 I use relu activation on all but the last layer

```
# import tensorflow and keras (tf.keras not "vanilla" Keras)
import tensorflow as tf
from tensorflow import keras
# get data
(train_images, train_labels), (test_images,
                                test_labels) = keras.datasets.mnist.load_data()

# setup model
model = keras.Sequential([
    keras.layers.Flatten(input_shape=(28, 28)),
    keras.layers.Dense(128, activation=tf.nn.relu),
    keras.layers.Dense(64, activation= tf.nn.relu),
    keras.layers.Dense(10, activation=tf.nn.softmax)
])

model.compile(optimizer=tf.optimizers.Adam(),
              loss='sparse_categorical_crossentropy',
              metrics=['accuracy'])

# train models
model.fit(train_images, train_labels, epochs=5)

print('\n Evaluation' )
# evaluate
test_loss, test_acc = model.evaluate(test_images, test_labels)
print('test accuracy:', test_acc)
# make predictions
predictions = model.predict(test_images)
```

```
Epoch 1/5
1875/1875 ————— 6s 3ms/step - accuracy: 0.8124 - loss: 4.6972
Epoch 2/5
1875/1875 ————— 4s 2ms/step - accuracy: 0.9239 - loss: 0.3186
Epoch 3/5
1875/1875 ————— 5s 2ms/step - accuracy: 0.9464 - loss: 0.2017
Epoch 4/5
1875/1875 ————— 5s 2ms/step - accuracy: 0.9548 - loss: 0.1581
Epoch 5/5
1875/1875 ————— 4s 2ms/step - accuracy: 0.9610 - loss: 0.1388

Evaluation
313/313 ————— 1s 3ms/step - accuracy: 0.9592 - loss: 0.1602
test accuracy: 0.9621999859809875
313/313 ————— 1s 2ms/step
```



We now see the output. What can we say

- 1 We overfit
- 2 There are 313 points in the test set
- 3 There are 10 000 points in the test set
- 4 1875 is about 6 times 313
- 5 the loss is the accuracy
- 6 the loss decreases along the trajectory

```
model.summary()
```

Model: "sequential"

Layer (type)	Output Shape	Param #
flatten (Flatten)	(None, 784)	0
dense (Dense)	(None, 128)	100480
dense_1 (Dense)	(None, 64)	8256
dense_2 (Dense)	(None, 10)	650
Total params: 109,386		
Trainable params: 109,386		
Non-trainable params: 0		

Explain the number of parameters on each layer

```
model.summary()
```

Model: "sequential"

Layer (type)	Output Shape	Param #
flatten (Flatten)	(None, 784)	0
dense (Dense)	(None, 128)	100480
dense_1 (Dense)	(None, 64)	8256
dense_2 (Dense)	(None, 10)	650
Total params: 109,386		
Trainable params: 109,386		
Non-trainable params: 0		

Outline

1 Goals

2 The first Neural Network: the Perceptron

- Logistic regression
- Discovering Fully connected NN through the NNPG.
- Formalization, advanced topics
- Further discussion

Intuition

Up to that point, we have seen :

- What a Neural Network was.
- How to implement it in Python.

Next Question: why and when does it work?

Intuition

Up to that point, we have seen :

- What a Neural Network was.
- How to implement it in Python.

Next Question: why and when does it work?

- ① Approximation theorem
- ② Optimization

Approximation Theorem

Goal

$$\min_{f \in \mathcal{F}_{\text{MLP}}} \frac{1}{n} \sum_{i=1}^n [\ell(f(X_i), Y_i)].$$

As said before, a MLP can output non-linear functions... But how powerful is it?

Approximation Theorem

Goal

$$\min_{f \in \mathcal{F}_{\text{MLP}}} \frac{1}{n} \sum_{i=1}^n [\ell(f(X_i), Y_i)].$$

As said before, a MLP can output non-linear functions... But how powerful is it?

Continuous Neural Networks with one single hidden layer and any bounded and non constant activation function can approximate any function in L^p , provided a sufficient number of hidden units.

↪ Very powerful in terms of approximations.

Not very surprising: non linear function with millions of parameters!

Optimization - Fitting the network

Goal

$$\min_{f \in \mathcal{F}_{\text{MLP}}} \frac{1}{n} \sum_{i=1}^n [\ell(f(X_i), Y_i)].$$

How to minimize a function?

Gradient Methods. = cheapest way to **update (learn) the weights iteratively** to **minimize the loss**.

Optimization - Fitting the network


Goal

$$\min_{f \in \mathcal{F}_{\text{MLP}}} \frac{1}{n} \sum_{i=1}^n [\ell(f(X_i), Y_i)].$$


Gradient Methods. = cheapest way to update (learn) the weights iteratively to minimize the loss.

Two “miracles”:

- ① Autodifferentiation: even though the function is very complex and high dimensional, it is possible to compute gradients!
- ② Optimization seems to work ok, though the function is non convex - we do not end up in too bad local minima. (specialized optim algos: Adam, AdaDelta, etc.)



These 2 miracles make it possible to learn a good regressor/classifier with NN and to benefit from the powerful approximation properties



Learning:
by GD.

Define a risk:
ERM $R(\hat{f}_n, X_{\text{train}}, Y_{\text{train}})$ - minimize it

Iteratively improve $\hat{f}_n$ within the class of allowed fct's.

take a training point X^p
compute $\hat{f}_n(X^p) = \hat{y}^p$
 $X^p \rightarrow [] \rightarrow \hat{y}^p$
 compare to y^p
 improve the weights $\times 10^4$

Conclusion

Neural networks :

- ① learn very complex non linear functions in high dimension
- ② can approximate nearly any function
- ③ can be optimized even though highly non convex.

Are thus expected to work:

- When depth or width increases.
- Thus with very large datasets
- Requiring a lot of computational power.

⇒ Explains why they were so successful since 2010

Conclusion

Neural networks :

- ① learn very complex non linear functions in high dimension
- ② can approximate nearly any function
- ③ can be optimized even though highly non convex.

Are thus expected to work:

- When depth or width increases.
- Thus with very large datasets
- Requiring a lot of computational power.

⇒ Explains why they were so successful since 2010

What my layer wants me to say: we haven't talked about many points !!

- Initialization
- Regularization

Conclusion

Neural networks :

- ① learn very complex non linear functions in high dimension
- ② can approximate nearly any function
- ③ can be optimized even though highly non convex.

Are thus expected to work:

- When depth or width increases.
- Thus with very large datasets
- Requiring a lot of computational power.

⇒ Explains why they were so successful since 2010

What my layer wants me to say: we haven't talked about many points !!

- Initialization
- Regularization

Next:

- Brief history
- How to use the structure?

A brief history of NN

- 1943: Neural networks
- 1957: Perceptron
- 1974-86: Backpropagation, RBM, RNN
- 1989-98: CNN, MNIST
- 2009: ImageNet
- 2012: AlexNet,
- 2014: GANss
- 2016: AlphaGo
- 2018: BERT

The Computational power made the major change (+ investment and creativity).

Directions

- When does it work?

Large or huge datasets. Structured tasks.

↪ **Images and text.**

⚠ do not try to apply DL everywhere

Each application requires a special architecture:

- Images : **Convolutional Neural Network (CNN)**.
- Text : **Recurrent Neural Networks (RNN) (2012-2018), Transformers (2018-2024)**.